FACTORY PRE-INSTALLED SILICONE CABLES













- > FACTORY PRE-INSTALLED SILICONE CABLES FOR DURABILITY
- > SILICONE JACKET TO PROTECT FROM HEAT, CUTS AND SPATTER
- LED'S ON THE END FOR FAST AND EASY TROUBLESHOOTING
- PTFE COATED NUTS FOR SPATTER RESISTANCE
- INSIDE CABLE IS MADE OF TPE FOR EXTENDED DURABILITY
- > IDEAL FOR USE IN WELD CELLS WHERE CABLES CAN GET DAMAGED

FACTORY PRE-INSTALLED SILICONE CABLES SPECIFICATIONS

	DOUBLE-ENDED	DOUBLE-ENDED	DOUBLE-ENDED	DOUBLE-ENDED	SPLITTER
	Double-Ended Cable	Double-Ended Cable	Double-Ended Cable	Double-Ended Cable	Splitter Cable
Male Connector	straight	straight	angled	angled	straight
Female Connector	straight	angled	straight	angled	straight
Cable Material	TPE	TPE	TPE	TPE	TPE
Protective Cable Jacket	Silicone Tube	Silicone Tube	Silicone Tube	Silicone Tube	Silicone Tube
Locking Nuts	PTFE Coated	PTFE Coated	PTFE Coated	PTFE Coated	PTFE Coated
LED on Female End	Power and Output	Power and Output	Power and Output	Power and Output	
M12, 4-pin - 0.6 m PNP	R-MS4TZ-T070.6+ R-FS4/3TP-T070.6-S	R-MS4TZ-T070.6+ R-FA4/3TP-T070.6-S	R-MA4TZ-T070.6+ R-FS4/3TP-T070.6-S	R-MA4TZ-T070.6+ R-FA4/3TP-T070.6-S	
M12, 4-pin - 0.6 m no LED	R-MS4TZ-T070.6+ R-FS4TZ-T070.6-S	R-MS4TZ-T070.6+ R-FA4/3TZ-T070.6-S	R-MA4TZ-T070.6+ R-FS4/3TZ-T070.6-S	R-MA4TZ-T070.6+ R-FA4/3TZ-T070.6-S	U2-R4R-FS4KZ- T070.6-S
M12, 4-pin- 2.0 m PNP	R-MS4TZ-T072+ R-FS4/3TP-T072-S	R-MS4TZ-T072+ R-FA4/3TP-T072-S	R-MA4TZ-T072+ R-FS4/3TP-T072-S	R-MA4TZ-T072+ R-FA4/3TP-T072-S	
M12, 4-pin - 2.0 m no LED	R-MS4TZ-T072+ R-FS4TZ-T072-S	R-MS4TZ-T072+ R-FA4TZ-T072-S	R-MA4TZ-T0702+ R-FS4TZ-T072-S	R-MA4TZ-T0702+ R-FA4TZ-T072-S	U2-R4R-FS4KZ- T072-S
NPN is available, change "P" to					
M8 connectors are available or	n either or both ends				

FACTORY PRE-INSTALLED SILICONE CABLES ARE THE BEST CHOICE FOR EXTRA DURABILITY IN WELD CELLS WHERE CABLES ARE EXPOSED TO HIGH HEAT, WELD SPATTER, AND SHARP TOOLS OR PARTS.



In Canada: 3419 Mainway, Burlington, ON L7M 1A9
In the USA: 1889 Maryland Ave., Niagara Falls, NY 14304

Toll Free: 1-800-644-1756
SENSORS service@htmsensors.com

Proudly Supported by

