


- SILICONE TUBING AND EXPANDABLE SLEEVING FOR SENSOR AND CABLE PROTECTION
- AVAILABLE IN MANY INNER DIAMETERS
- CLEAR SILICONE TO MAINTAIN VISIBILITY TO CABLES AND SENSORS
- SILICONE RUBBER OVER FIBERGLASS BRAID SLEEVING FOR IRREGULAR SHAPED CABLES AND WIRING
- IDEAL FOR PROTECTION FROM HEAT, CUTS AND WELD SPATTER
- AVAILABLE PRE-INSTALLED ON SENSORS AND CABLE PRODUCTS

## SILICONE WELD SPATTER PROTECTION SPECIFICATIONS



CLEAR SILICONE TUBING - TEMPERATURE RATING: 500 °F / 260 °C			
PART NUMBER	INNER DIAMETER	OUTER DIAMETER	COIL LENGTH
HSCP-0375	0.375"	0.500"	100 ft.
HSCP-0500	0.500"	0.625"	50 ft.
HSCP-0625	0.625"	0.750"	50 ft.
HSCP-0750	0.750"	0.875"	50 ft.
HSCP-1000	1.000"	1.125"	50 ft.



CLEAR SILICONE TUBING AND SELF-FUSING SILICONE TAPE ARE PROVEN TO REDUCE DOWNTIME IN WELD CELLS BY PROTECTING CABLES, CONNECTORS AND SENSORS.

EXPANDABLE SLEEVING - TEMPERATURE RATING: -55 °C to +200 °C (-67 °F to 392 °F)		
PART NUMBER	INNER DIAMETER	SPOOL LENGTH
BSST-02-100	1.9 mm	100 ft.
BSST-03-100	3.0 mm	100 ft.
BSST-04-100	4.2 mm	100 ft.
BSST-06-100	5.94 mm	100 ft.
BSST-08-100	8.38 mm	100 ft.
BSST-10-100	9.52 mm	100 ft.
BSST-12-100	12.70 mm	100 ft.
BSST-16-100	15.87 mm	100 ft.



EXPANDABLE SLEEVING IS THE IDEAL SILICONE SLEEVING SOLUTION FOR A BROAD RANGE OF APPLICATIONS, ESPECIALLY THOSE REQUIRING A SNUG FIT OVER MORE IRREGULARLY SHAPED CABLE AND WIRING COMPONENTS.

