# V-CFA2V/R2C-V535

# Note: The product images shown may change over time as

Diagram



Part Number

products are updated.

### V-CFA2V/R2C-V535

## Features

HTM Sensors stocks thousands of sensor cables for convenient same-day-shipping. Standard M8 and M12 cables have the best prices in the industry and are always available and in stock for customer requirements.

# New advances in sensor cables allow for extended durability and longevity in the harshest environments.

# Wiring



# Technical Data

Technical Data	
Connector Type	Form C EN175301-803
Cable Type	Single Ended
Connector A	-
Connector B	Female Angled
Contact Spacing	8 mm
Number of Poles	2 + 2PE
Earth Position	12 & 6
Jacket Type	PVC
Length	5 m
Body Material	Polypropylene
Contact Carrier	PA66
Circuit Type	Varistor + Bipolar Red LED
Gasket	NBR
Fixing Screw Size	M2.5x0.5 L22.5 mm
Fixing Screw Material	Fe/Zn
Rated Voltage	115 V
Rated Current	6A
Protection Class	IP67
Temperature Rating	-20 °C to +80 °C
Wire Gauge	3 x 22 AWG





In the USA: 1889 Maryland Ave., Niagara Falls, NY 14305 In Canada: 3419 Mainway, Burlington, ON L7M 1A9 Toll Free: 1-800-644-1756 • Fax: 888-283-2127 service@htmsensors.com

htmsensors.com

# Cables and Connectors -Solenoid Cables