





Note: The product images shown may change over time as products are updated.

Dimensions




Connection

Male insert M12



2x female insert M8



Part Number

U2-R4C-FS3KZ-T661


Features

- High performance TPE cables for automotive applications
- 10 Million flex rating for long-lasting performance
- Anti-vibration nuts for reliable connection
- Single-ended, double-ended and splitter versions available
- Ideal for use in weld cells where cables can get damaged

Technical Data

Connector Type	M12
Cable Type	Splitter
Connector A	Male Straight
Connector B	2 x M8 Female Straight
Length (m)	1 m
Locking System	Screw
Rated Current	4 A
Rated Voltage	250 V
Wire Gauge	4 x 22 AWG
Stranding	19 x 34
Contact Carrier	PUR
Molded Body	PUR
Contact Material	CuSn (Bronze)
Contact Plating	Au (Gold)
Jacket Type	TPE-E
Coupling Nut	M12 - PTFE Brass, M8 - Die Cast Zinc, Nickel Plated
Protection Class	IP68
Temperature Range	-25 °C to +105 °C

Cable Design



In the USA: 1889 Maryland Ave., Niagara Falls, NY 14305
 In Canada: 3419 Mainway, Burlington, ON L7M 1A9
 Toll Free: 1-800-644-1756 • Fax: 888-283-2127
 service@htmsensors.com