

1 XB-C100BK + XB-C101BK

XB-C100-BK



Upper Connector

(M30 x 1.5 upper thread & M20 x 1.5 lower thread)

XB-C101-BK



Lower Connector

(M20 x 1.5 inner M30 x 1.5 external)

2 XB-E60, XB-E150, XB-E300, XB-E600 (60 mm, 150 mm, 300 mm, 600 mm)



Model	Length (mm)	Material Color
XB-E60-BK	60	Aluminum, Black
XB-E150-BK	150	Aluminum, Black
XB-E300-BK	300	Aluminum, Black
XB-E600-BK	600	Aluminum, Black

3 XB-H100 Plate, XB-P100 Swivel base, XS-C100 L-Bracket, XS-C101+XS-C110 Bracket Kit

XB-H100-BK



XB-P100-BK



XS-C100



XS-C101+XS-C110



For White, change BK to WH



MODULAR LED TOWER LIGHTS

	Model	Buzzer	- Segments	Colors	- Connection	/ Special Options
Example Part Number	HLT70	B	- S3	RYG	- 2M	/ WH=White
Options Available	HLT70=70 mm dia tower light HLT50=50 mm dia tower light	Blank=without Buzzer B=with Buzzer	- S1= 1 Segment S2= 2 Segment S3= 3 Segment S4= 4 Segment S5= 5 Segment (no buzzer option)	R=Red / Y=Yellow / G=Green / B=Blue / W=White *List colors from top to bottom Segments	- 2M=Pre-wired Cable Length P12=M12 Pigtail* *3 stack without Buzzer is M12 4-Pin 3 segment with Buzzer and 4 segment without Buzzer is M12 5-pin 4 segment with Buzzer and 5 segment without Buzzer is M12 8-pin	/




SIGNAL COLUMN LIGHTS

	Model	Buzzer	- Colors	- Connection	/ Special Options
Example Part Number	HLC50	B	- RYGB	- 2M	/ WH=White
Options Available	HLC50=50 mm light column	Blank=without Buzzer B=with Buzzer	- R=Red / Y=Yellow / G=Green / B=Blue	- 2M=Pre-wired Cable Length P12=M12 Pigtail* *Without Buzzer is M12 4-Pin With Buzzer is M12 5-Pin	



QUAD-COLORED LED INDICATOR LIGHTS

	Model	Buzzer	- Colors	- Connection	/ Special Options
Example Part Number	HL50	B	- RYGB	- 2M	/ WH=White
Options Available	HL22=22 mm dia dome HL30=30 mm dia dome HL50= 50 mm dia dome HL90= 90 mm dia dome	Blank=without Buzzer B=with Buzzer (HL50 only)	- R=Red / Y=Yellow / G=Green / B=Blue 	- 2M=Pre-wired Cable Length P12=M12 Pigtail	



COLORED LED TOUCH BUTTONS

	Model	Function	Output Type	- Colors	- Connection
Example Part Number	HL50	T	P	- GR	- 2M
Options Available	HL50=50 mm dia dome HL30=30 mm dia dome	T=Touch TF1=Touch Function 1 TF2=Touch Function 2	P=PNP N=NPV	First colour listed is job colour, second colour is the touch colour R=Red / Y=Yellow / G=Green / B=Blue	- 2M=Pre-wired Cable Length P12=0.3 m, M12 A-Coded Pigtail

Touch Function=	Only one colour is required Job Colour Illuminated at all times while job input is active Touch Activates output
Touch Function 1=	Two colours are required Job and Touch Job Colour is illuminated while Job input is active Touch Activates the output and overrides the Job colour with the Touch colour
Touch Function 2=	Two colours are required Job and Touch Job Colour is illuminated while Job input is active Touch Activates the output If Job Input is not active and unit is touched, Touch colour is illuminated