

HTMTM
SENSORS



- FACTORY PRE-INSTALLED SILICONE CABLES FOR DURABILITY
- SILICONE JACKET TO PROTECT FROM HEAT, CUTS AND SPATTER
- LED'S ON THE END FOR FAST AND EASY TROUBLESHOOTING
- PTFE COATED NUTS FOR SPATTER RESISTANCE
- INSIDE CABLE IS MADE OF TPE FOR EXTENDED DURABILITY
- IDEAL FOR USE IN WELD CELLS WHERE CABLES CAN GET DAMAGED

FACTORY PRE-INSTALLED SILICONE CABLES SPECIFICATIONS



	Double-Ended Cable	Double-Ended Cable	Double-Ended Cable	Double-Ended Cable	Splitter Cable
MALE CONNECTOR	Straight	Straight	Angled	Angled	Straight
FEMALE CONNECTOR	Straight	Angled	Straight	Angled	Straight
CABLE MATERIAL	TPE	TPE	TPE	TPE	TPE
PROTECTIVE CABLE JACKET	Silicone Tube	Silicone Tube	Silicone Tube	Silicone Tube	Silicone Tube
LOCKING NUTS	PTFE Coated	PTFE Coated	PTFE Coated	PTFE Coated	PTFE Coated
LED ON FEMALE END	Power and Output	Power and Output	Power and Output	Power and Output	
PART NUMBERS					
M12, 4-pin - 0.6 m PNP	R-MS4TZ-T070.6+ R-FS4/3TP-T070.6-S	R-MS4TZ-T070.6+ R-FA4/3TP-T070.6-S	R-MA4TZ-T070.6+ R-FS4/3TP-T070.6-S	R-MA4TZ-T070.6+ R-FA4/3TP-T070.6-S	
M12, 4-pin - 0.6 m no LED	R-MS4TZ-T070.6+ R-FS4TZ-T070.6-S	R-MS4TZ-T070.6+ R-FA4/3TZ-T070.6-S	R-MA4TZ-T070.6+ R-FS4/3TZ-T070.6-S	R-MA4TZ-T070.6+ R-FA4/3TZ-T070.6-S	U2-R4R-FS4KZ- T070.6-S
M12, 4-pin - 2.0 m PNP	R-MS4TZ-T072+ R-FS4/3TP-T072-S	R-MS4TZ-T072+ R-FA4/3TP-T072-S	R-MA4TZ-T072+ R-FS4/3TP-T072-S	R-MA4TZ-T072+ R-FA4/3TP-T072-S	
M12, 4-pin - 2.0 m no LED	R-MS4TZ-T072+ R-FS4TZ-T072-S	R-MS4TZ-T072+ R-FA4TZ-T072-S	R-MA4TZ-T0702+ R-FS4TZ-T072-S	R-MA4TZ-T0702+ R-FA4TZ-T072-S	U2-R4R-FS4KZ- T072-S
NPN is available, change "P" to "N" in part number.					
Custom lengths and connector styles are available.					
M8 connectors are available on either or both ends.					

NOTE: Specifications subject to change without notification.

FACTORY PRE-INSTALLED SILICONE CABLES ARE THE BEST CHOICE FOR EXTRA DURABILITY IN WELD CELLS WHERE CABLES ARE EXPOSED TO HIGH HEAT, WELD SPATTER, AND SHARP TOOLS OR PARTS.

