













- > QUICK-CONNECT SENSOR CABLES FOR SENSOR CONNECTIONS
- LOW PRICES WITH THOUSANDS IN STOCK FOR SAME-DAY SHIPPING
- AVAILABLE IN LOW-COST PVC, OIL-RESISTANT PUR, AND SPATTER-RESISTANT TPE
- > AVAILABLE IN YELLOW, BLACK OR GREY OR CUSTOM COLORS
- AVAILABLE IN STANDARD 5 m LENGTH, OR ANY CUSTOM LENGTH
- > ANY STYLE AVAILABLE WITH PRE-INSTALLED PROTECTIVE SILICONE JACKET

QUICK-CONNECT SENSOR CABLES - M12 SPECIFICATIONS



| M12 PVC | | M12 PUR | | M12 TPE | |
|-------------------------------------|--|--|---|----------------------------------|---|
| Female Straight | Female Angled | Female Straight | Female Angled | Female Straight | Female Angled |
| Low-Cost PVC | | Oil-Resistant PUR | | Weld Spatter Resistant TPE | |
| | | 22 / | AWG | | |
| Nickel-plated Brass | | | PTFE Coated Brass | | |
| | | 250 V AC/300 V DC (10 | 0-30 V DC LED models) | | |
| IP68 | | | | | |
| | | | | | |
| R-FS4TZ-V075 | R-FA4TZ-V075 | R-FS4TZ-P665 | R-FA4TZ-P665 | R-FS4TZ-T665 | R-FA4TZ-T665 |
| R-FS4/3TP-V075 | R-FA4/3TP-V075 | | | | |
| R-FS4/3TN-V075 | R-FA4/3TN-V075 | | | | |
| R-FS5TZ-V075 | R-FA5TZ-V075 | R-FS5TZ-Y075 | R-FA5TZ-Y075 | | |
| R-FS8TZ-V075 | R-FA8TZ-V075 | R-FS8TZ-Y095 | R-FA8TZ-Y095 | | |
| Add -SS on the end of | the part # | | | | |
| Add -PTFE on the end of the part # | | | | | |
| Add -18AWG on the end of the part # | | | | | |
| Add - S on the end of t | he part # | | | | |
| Change "5" on the end | d of the part # to the desired I | ength in meters | | | |
| Change "F" in the part | # to "M" | | | | |
| For PVC Cables, add - | Black, -Grey, -Yellow, or -Ora | nge to the end of the part | # | | |
| | R-FS4TZ-V075 R-FS4/3TP-V075 R-FS4/3TN-V075 R-FS5TZ-V075 Add -SS on the end of Add -PTFE on the end Add -18AWG on the end Add -S on the end of the end Change "5" on the end Change "F" in the part For PVC Cables, add - | R-FS4TZ-V075 R-FA4TZ-V075 R-FS4/3TP-V075 R-FA4/3TP-V075 R-FS4/3TN-V075 R-FA4/3TN-V075 R-FS5TZ-V075 R-FA5TZ-V075 R-FS8TZ-V075 R-FA8TZ-V075 Add -SS on the end of the part # Add -PTFE on the end of the part # Add -18AWG on the end of the part # Add -S on the end of the part # Change "5" on the end of the part # to the desired Change "F" in the part # to "M" | Low-Cost PVC Oil-Resis 22 / Nickel-plated Brass 250 V AC/300 V DC (10 P R-FS4TZ-V075 R-FA4TZ-V075 R-FS4TZ-P665 R-FS4/3TP-V075 R-FA4/3TP-V075 R-FS5TZ-V075 R-FA4/3TN-V075 R-FS5TZ-V075 R-FA5TZ-V075 R-FS5TZ-Y075 R-FS8TZ-V075 R-FA8TZ-V075 R-FS8TZ-Y095 Add -SS on the end of the part # Add -PTFE on the end of the part # Add -18AWG on the end of the part # Add - S on the end of the part # Change "5" on the end of the part # to the desired length in meters Change "F" in the part # to "M" For PVC Cables, add - Black, -Grey, -Yellow, or -Orange to the end of the part s | Low-Cost PVC Oil-Resistant PUR | Low-Cost PVC Oil-Resistant PUR Weld Spatter |

NOTE: Specifications subject to change without notification.

QUICK-CONNECT SENSOR CABLES HAVE A LOW PRICE, AND THOUSANDS IN STOCK FOR SAME DAY SHIPPING.

