



- HIGH PERFORMANCE TPE CABLES FOR AUTOMOTIVE APPLICATIONS
- 10 MILLION FLEX RATING FOR LONG-LASTING PERFORMANCE
- ANTI-VIBRATION NUTS FOR RELIABLE CONNECTION
- PTFE COATED NUTS FOR SPATTER RESISTANCE
- SINGLE-ENDED, DOUBLE-ENDED AND SPLITTER VERSIONS AVAILABLE
- IDEAL FOR USE IN WELD CELLS WHERE CABLES CAN GET DAMAGED



HIGH PERFORMANCE TPE AUTOMOTIVE CABLES SPECIFICATIONS



	Double-Ended Cable	Double-Ended Cable	Double-Ended Cable	Double-Ended Cable	Splitter Cable
MALE CONNECTOR	Straight	Straight	Angled	Angled	Straight
FEMALE CONNECTOR	Straight	Angled	Straight	Angled	Straight
CABLE MATERIAL	TPE	TPE	TPE	TPE	TPE
FLEX RATING	10 Million Cycles per Mil-C-13777G	10 Million Cycles per Mil-C-13777G	10 Million Cycles per Mil-C-13777G	10 Million Cycles per Mil-C-13777G	10 Million Cycles per Mil-C-13777G
ANTI-VIBRATION NUTS	PTFE Coated	PTFE Coated	PTFE Coated	PTFE Coated	PTFE Coated
PART NUMBERS					
M12, 4-pin - 0.6 m	R-MS4TZ-T660.6+ R-FS4TZ-T660.6	R-MS4TZ-T660.6+ R-FA4TZ-T660.6	R-MA4TZ-T660.6+ R-FS4TZ-T660.6	R-MA4TZ-T660.6+ R-FA4TZ-T660.6	U2-R4R-FS4KZ-T660.6
M12, 4-pin - 2.0 m	R-MS4TZ-T662+ R-FS4TZ-T662	R-MS4TZ-T662+ R-FA4TZ-T662	R-MA4TZ-T662+ R-FS4TZ-T662	R-MA4TZ-T662+ R-FA4TZ-T662	U2-R4R-FS4KZ-T662
Custom lengths and connector styles are available					
M8 connectors are available on either or both ends					

NOTE: Specifications subject to change without notification.

HIGH PERFORMANCE TPE AUTOMOTIVE CABLES ARE THE BEST CHOICE FOR EXTRA DURABILITY IN WELD CELLS WHERE CABLES ARE EXPOSED TO HIGH HEAT, WELD SPATTER AND SHARP TOOLS OR PARTS.

